**User Manual**

G211F – 3U CompactPCI® Serial Quad Fiber Optics Interface


Configuration example

G211F - 3U CompactPCI® Serial Quad Fiber Optics Interface

The G211F is a rugged 3U CompactPCI® Serial peripheral board. It offers the possibility to implement four optical fiber Ethernet interfaces. The board is equipped with a cage for connection of four SFP transceivers. The cage hosts the optical adapter. The cables are connected to the adapter module. MEN offers an optical transceiver with LC-Duplex connectors as an accessory.

All four interfaces are controlled by one Ethernet controller which is connected to the backplane via a x4 PCI Express® link and supports the IEEE 802.3x standard. Each interface supports a data transfer rate of 1000 Mbit/s if all interfaces are used simultaneously. Two LEDs show the link and activity status of every interface.

The G211F can be used in combination with a CompactPCI® Serial or CompactPCI® PlusIO CPU board in a CompactPCI® Serial or hybrid system. It is screened for extended operating temperature and prepared for conformal coating for use in harsh and mobile environments.

Diagram

Technical Data

Ethernet Interfaces

- Four 1000Base-SX interfaces
- IEEE802.3x support
  - Full-duplex flow control
  - 1 Gbit/s data transfer rate for each interface when all 4 interfaces are used simultaneously
- 4x2 status LEDs to signal link status and activity

Front Connections

- Four SFP slots

CompactPCI® Serial

- Compliance with CompactPCI® Serial PICMG CPCI-S.0 Specification
- Peripheral slot
- Host interface: One PCI Express® x4 link
  - PCIe® 2.0 support
  - Data rate up to 2 GB/s in each direction (5 Gbit/s per lane)

Electrical Specifications

- Isolation voltage: 500V between Ethernet links and between Ethernet links and shield or ground
- Supply voltage/power consumption:
  - +12V (-5%/+5%), 3.65 W typ./ 8 W max.

Mechanical Specifications

- Dimensions: conforming to CompactPCI® Serial specification for 3U boards
- Weight: 216 g (with heat sink)

Environmental Specifications

- Temperature range (operation):
  - -40..+85°C (screened)
  - Airflow: min. 1.0 m/s
- Temperature range (storage): -40..+85°C
- Relative humidity (operation): max. 95% non-condensing
- Relative humidity (storage): max. 95% non-condensing
- Altitude: -300 m to + 3,000 m
- Shock: 50 m/sð, 30 ms
- Vibration (Function): 1 m/sð, 5 Hz – 150 Hz
- Vibration (Lifetime): 7.9 m/sð, 5 Hz – 150 Hz
- Conformal coating on request

MTBF

- MTBF: 311,742h @ 40°C according to IEC/TR 62380 (RDF 2000)

Safety

- PCB manufactured with a flammability rating of 94V-0 by UL recognized manu-facturers

EMC

- Tested according to EN 55022 (radio disturbance), EN 61000-4-2 (ESD) and EN 61000-4-3 (HF irradiation)

Software Support

- Windows®
- Linux
- For more information on supported operating system versions and drivers see online data sheet.

Configuration Options

Ethernet

- Two single SFP cages (ruggedized) on 8HP
- Four single SFP cages (ruggedized) on 16HP

Cooling Concept

- Also available with conduction cooling in MEN CCA frame

Please note that some of these options may only be available for large volumes. Please ask our sales staff for more information.

For available standard configurations see online data sheet.

Product Safety

⚠️ **Electrostatic Discharge (ESD)**

Computer boards and components contain electrostatic sensitive devices. Electrostatic discharge (ESD) can damage components. To protect the board and other components against damage from static electricity, you should follow some precautions whenever you work on your computer.

- Power down and unplug your computer system when working on the inside.
- Hold components by the edges and try not to touch the IC chips, leads, or circuitry.
- Use a grounded wrist strap before handling computer components.
- Place components on a grounded antistatic pad or on the bag that came with the component whenever the components are separated from the system.
- Store the board only in its original ESD-protected packaging. Retain the original packaging in case you need to return the board to MEN for repair.

About this Document

This user manual is intended only for system developers and integrators, it is not intended for end users.

It describes the hardware functions of the board, connection of peripheral devices and integration into a system. It also provides additional information for special applications and configurations of the board.

The manual does not include detailed information on individual components (data sheets etc.). A list of literature is given in the appendix.

History

Issue	Comments	Date
E1	First issue	2011-04-21
E2	Changed Technical Data on page 4	2014-02-07

Conventions

This sign marks important notes or warnings concerning the use of voltages which can lead to serious damage to your health and also cause damage or destruction of the component.

This sign marks important notes or warnings concerning proper functionality of the product described in this document. You should read them in any case.

italics Folder, file and function names are printed in *italics*.

bold **Bold** type is used for emphasis.

monospace A `monospaced` font type is used for hexadecimal numbers, listings, C function descriptions or wherever appropriate. Hexadecimal numbers are preceded by "0x".

comment Comments embedded into coding examples are shown in green color.

hyperlink Hyperlinks are printed in blue color.

The globe will show you where hyperlinks lead directly to the Internet, so you can look for the latest information online.

IRQ# /IRQ Signal names followed by "#" or preceded by a slash ("/") indicate that this signal is either active low or that it becomes active at a falling edge.

in/out Signal directions in signal mnemonics tables generally refer to the corresponding board or component, "in" meaning "to the board or component", "out" meaning "coming from it".

Vertical lines on the outer margin signal technical changes to the previous issue of the document.

Legal Information

Changes

MEN Mikro Elektronik GmbH ("MEN") reserves the right to make changes without further notice to any products herein.

Warranty, Guarantee, Liability

MEN makes no warranty, representation or guarantee of any kind regarding the suitability of its products for any particular purpose, nor does MEN assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including, without limitation, consequential or incidental damages. TO THE EXTENT APPLICABLE, SPECIFICALLY EXCLUDED ARE ANY IMPLIED WARRANTIES ARISING BY OPERATION OF LAW, CUSTOM OR USAGE, INCLUDING WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE OR USE. In no event shall MEN be liable for more than the contract price for the products in question. If buyer does not notify MEN in writing within the foregoing warranty period, MEN shall have no liability or obligation to buyer hereunder.

The publication is provided on the terms and understanding that:

1. MEN is not responsible for the results of any actions taken on the basis of information in the publication, nor for any error in or omission from the publication; and

2. MEN is not engaged in rendering technical or other advice or services.

MEN expressly disclaims all and any liability and responsibility to any person, whether a reader of the publication or not, in respect of anything, and of the consequences of anything, done or omitted to be done by any such person in reliance, whether wholly or partially, on the whole or any part of the contents of the publication.

Conditions for Use, Field of Application

The correct function of MEN products in mission-critical and life-critical applications is limited to the environmental specification given for each product in the technical user manual. The correct function of MEN products under extended environmental conditions is limited to the individual requirement specification and subsequent validation documents for each product for the applicable use case and has to be agreed upon in writing by MEN and the customer. Should the customer purchase or use MEN products for any unintended or unauthorized application, the customer shall indemnify and hold MEN and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim or personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that MEN was negligent regarding the design or manufacture of the part. In no case is MEN liable for the correct function of the technical installation where MEN products are a part of.

Trademarks

All products or services mentioned in this publication are identified by the trademarks, service marks, or product names as designated by the companies which market those products. The trademarks and registered trademarks are held by the companies producing them. Inquiries concerning such trademarks should be made directly to those companies.

Conformity

MEN products are no ready-made products for end users. They are tested according to the standards given in the Technical Data and thus enable you to achieve certification of the product according to the standards applicable in your field of application.

RoHS

Since July 1, 2006 all MEN standard products comply with RoHS legislation.

Since January 2005 the SMD and manual soldering processes at MEN have already been completely lead-free. Between June 2004 and June 30, 2006 MEN's selected component suppliers have changed delivery to RoHS-compliant parts. During this period any change and status was traceable through the MEN ERP system and the boards gradually became RoHS-compliant.

WEEE Application

The WEEE directive does not apply to fixed industrial plants and tools. The compliance is the responsibility of the company which puts the product on the market, as defined in the directive; components and sub-assemblies are not subject to product compliance.

In other words: Since MEN does not deliver ready-made products to end users, the WEEE directive is not applicable for MEN. Users are nevertheless recommended to properly recycle all electronic boards which have passed their life cycle.

Nevertheless, MEN is registered as a manufacturer in Germany. The registration number can be provided on request.

Contents

Figures

Tables

1 Getting Started

This chapter gives an overview of the board and some hints for first installation in a system.

1.1 Map of the Board

Figure 1. *Map of the board – front panel*

Figure 2. *Map of the board – top view*

1.2 Integrating the Board into a System

You can use the following "check list" when installing the G211F in a CompactPCI Serial system for the first time.

☑ Power-down the system.

☑ Insert the G211F into a peripheral slot of your CompactPCI Serial system, making sure that the CompactPCI Serial connectors are properly aligned.

   Note: The peripheral slots of every CompactPCI Serial system are marked by a circle ○ on the backplane and/or at the front panel.

☑ Plug the desired SFP modules into the front panel slots of the G211F.

☑ Power-up the system.

☑ You can now install driver software.

1.3 Installing Driver Software

For a detailed description on how to install driver software please refer to the respective documentation.

🌐 You can find any driver software available for download on MEN's website.

2 Functional Description

2.1 Power Supply

The G211F is supplied with a primary +12V voltage via the CompactPCI Serial connector P1.

2.2 Ethernet Interfaces

The G211F is equipped with a card cage for connecting 4 SFP transceiver modules to LC-Duplex connectors. This way, four optical fiber Gigabit Ethernet interfaces can be implemented. MEN offers an optical transceiver for Gigabit Ethernet (1.25GBd, 1000BASE-SX) as an accessory.

See MEN's website for ordering information.

The Ethernet interfaces are controlled by the Intel 82580 Dual/Quad Gigabit Ethernet Controller. All channels support 1000Base-T physical layers, and half-duplex and full-duplex operation complying with IEEE802.3x. All four channels reach a performance of 1000 Mbit/s read and/or write when used simultaneously.

The unique MAC address for every interface is set at the factory and should not be changed. Any attempt to change this address may create node or bus contention and thereby render the board inoperable. The MAC addresses on G211F are:

- Interface X1: `0x 00 C0 3A A4 7x xx - 0x 00 C0 3A A4 7F FF`
- Interface X2: `0x 00 C0 3A A4 8x xx - 0x 00 C0 3A A4 8F FF`
- Interface X3: `0x 00 C0 3A A4 9x xx - 0x 00 C0 3A A4 9F FF`
- Interface X4: `0x 00 C0 3A A4 Ax xx - 0x 00 C0 3A A4 AF FF`

where "00 C0 3A" is the MEN vendor code, "A4" is the MEN product code. The last four digits depend on the interface and the serial number of the product. The serial number is added to the offset, for example for X2:

• Serial number 0042: `0x xx xx = 0x8000 + 0x002A = 0x 80 2A`.

2.3   Status LEDs

The front panel includes two status LEDs for each channel. They signal the link and activity:

Table 1. *Status LEDs*

LED Color	LED State	Function
Yellow	Blinking	Activity (RX and TX)
Green	On	Link (all speeds**)**

2.4   CompactPCI Serial Interface

The G211F uses one PCI Express x4 link at the backplane according to the CompactPCI Serial specification (PICMG CPCI-S.0).

For the pin assignment and a detailed description of the signals refer to the CompactPCI Serial specification.

3 Appendix

3.1 Literature and Web Resources

- G211F data sheet with up-to-date information and documentation:
  www.men.de/products/02G211F.html

3.1.1 Ethernet

- Intel 82580 Dual/Quad Gigabit Ethernet Controller
  www. intel.com
- ANSI/IEEE 802.3-1996, Information Technology - Telecommunications and Information Exchange between Systems - Local and Metropolitan Area Networks - Specific Requirements - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications; 1996; IEEE
  www.ieee.org
- Charles Spurgeon's Ethernet Web Site
  Extensive information about Ethernet (IEEE 802.3) local area network (LAN) technology.
  www.ethermanage.com/ethernet/
- InterOperability Laboratory, University of New Hampshire
  This page covers general Ethernet technology.
  www.iol.unh.edu/services/testing/ethernet/training/

## 3.2 Finding out the Product's Article Number, Revision and Serial Number

MEN user documentation may describe several different models and/or design revisions of the G211F. You can find information on the article number, the design revision and the serial number on two labels attached to the board.

- **Article number:** Gives the product's family and model. This is also MEN's ordering number. To be complete it must have 9 characters.
- **Revision number:** Gives the design revision of the product.
- **Serial number:** Unique identification assigned during production.

If you need support, you should communicate these numbers to MEN.

***Figure 3.** Labels giving the product's article number, revision and serial number*

Complete article number

02G211F00
00.00.00

Revision number

641517

Serial number